

Materialverbrauch



Berechnung nach Bohrlochdurchmesser

Dichte BETONAMIT® [kg/dm³]

1.75

Bohrlochdurchmesser [mm]	Bohrlochvolumen [dm ³ /m]	BETONAMIT® [kg/m]
20	0.31	0.55
21	0.35	0.61
22	0.38	0.67
23	0.42	0.73
24	0.45	0.79
25	0.49	0.86
26	0.53	0.93
27	0.57	1.00
28	0.62	1.08
29	0.66	1.16
30	0.71	1.24
31	0.75	1.32
32	0.80	1.41
33	0.86	1.50
34	0.91	1.59
35	0.96	1.68
36	1.02	1.78
37	1.08	1.88
38	1.13	1.98
39	1.19	2.09
40	1.26	2.20
41	1.32	2.31
42	1.39	2.42
43	1.45	2.54
44	1.52	2.66
45	1.59	2.78
46	1.66	2.91
47	1.73	3.04
48	1.81	3.17
49	1.89	3.30
50	1.96	3.44
51	2.04	3.57
52	2.12	3.72
53	2.21	3.86
54	2.29	4.01
55	2.38	4.16
56	2.46	4.31
57	2.55	4.47
58	2.64	4.62
59	2.73	4.78
60	2.83	4.95